

::: HOME

::: ABOUT US

::: CONTACT

::: PRESS



::: PRODUCTS

::: DEALERS

::: NEWS

::: EVENTS

::: CASE STUDIES

::: LINKS

PRODUCT LINES



PDF DOWNLOADS :::

I-FLY SERIES :::

ASYM SERIES :::

COAXIAL SERIES :::

BASS ENCLOSURES :::

→ WMD 1803

→ SB 15

→ VSB 215

→ VSB 215 P

→ VSB 218

→ VSB 218 P

MONITORS :::

FULL FREQUENCY :::

SB15

The SB15 is essentially half a VSB215, it is highly compact and versatile sub bass speaker, ideal for small conference, pub gigs and installation work. Its low weight and well positioned handles make it ideal for "one man" jobs in the hire sector. With good frequency response from 30 to 200Hz it is well suited with a satellite mid high speaker such as the ASYM2S2 or soon to be released CX81 pole mounted above it.

The 1000W AES dual suspension, neodymium 15 inch woofer ensures fast attack times giving tight punchy bass and plenty of sub response.

The driver is angled down on its baffle giving asymmetry internally to reduce "booming" and to utilise the floor ahead of the cabinet as a partial horn, increasing the efficiency of the box.

High build quality is essential in any sub bass cabinet to ensure that the cabinet itself does not vibrate and soak up potential energy that could be delivered as intended out of the front of the box. The SB15 is no exception and is built entirely by hand in our workshop utilising 18mm birch ply and extensively routed glued and screwed throughout.



FEATURES

- highly portable size and weight
- well positioned handles
- high SPL output
- top hat mount
- hand built in 18mm birch ply

APPLICATIONS:

- small clubs / bars
- small hire / rental
- small band venues
- sidefill/drumfill
- conferences
- corporate events

PERMANENT INSTALLATION IN:

- pubs
- small night clubs and venues
- auditoriums
- theatres
- places of worship and sporting venues

TECHNICAL SPECIFICATION:

Type	Medium throw subwoofer
Frequency response	35Hz-225Hz +/- 3dB

ACCESSORIES



Noise Control Audio produce a range of wheelboards, speaker straps and covers to keep your stack secured and protected.

**For more information please call:
0208 808 1923**



Driver	1 x 15" (381 mm) 4" voice coil, dual suspension, vented gap
Power rating	1 x 1000W AES
Recommended amplifier	1250W @8 ohm
Sensitivity	97dB @1w/1m
Maximum SPL	127dB
Nominal impedance	8 ohms
Dispersion	100 x 80
Crossover points	35Hz and 150Hz
Connectors	2 x Neutrik NL4 Speakons

DIMENSIONS:

Height	500mm
Width	450mm
Depth	730mm
Weight	30Kg

CONSTRUCTION:

18mm Birch Ply
Finished in textured water resistant
Noise Control Audio Green
powder coated protective grill

Drawings to follow

 [download PDF DATA SHEET](#)



Click if you need to install Adobe Reader®